

ORANGE LINE


Get Rolling

OrangeLine: Trailering solutions for Kubota equipment





ORANGE LINE



OrangeLine Works as Hard as You Do



OrangeLine's professional-grade trailers are precision-engineered to help America's farmers, builders and workers get more out of their Kubota equipment.

Whether you're planting a field, manicuring a lawn or constructing a home, OrangeLine has your back. Right-sized, feature-rich and work-ready, OrangeLine Trailers deliver premium quality perfectly matched to the Kubota product line.

And with exclusive financing available through Kubota Finance, it's easy to bring home the equipment-and-trailer package that best fits your needs.



Package-Ready Trailers

OrangeLine Trailers were selected to perfectly match up with Kubota products, so you get a trailer that's built right for your equipment needs.



Quality, Professional-Grade Trailers

OrangeLine Trailers are designed to include top-of-the-line components and the features preferred by professional users.



3-Year Structural Warranty

Have peace of mind with your purchase knowing that OrangeLine Trailers are backed by a 3-Year Structural Warranty.



Kubota Financing Friendly

OrangeLine Trailers is an allied partner with Kubota — that means you can finance your OrangeLine Trailer with your Kubota equipment purchase.



SU Series | Single-Axle Utility Trailer

Compact and easy to tow, the SU Series offers heavy-duty performance at a smaller size, maximizing trailer maneuverability in tight spaces. A reinforced, spring-loaded rear ramp gate allows for quick loading and unloading of equipment. Perfect for landscaping, gardening and home DIY projects, the SU capably handles zero-turn mowers, Kubota RTVs and other utility vehicles.

SU35 | Single-Axle Utility Trailer



Standard SU-Series Features

- A** 2" A-Frame Coupler

B 2,000# Set-Back Jack with Sand Foot

C 2-3/8" OD Pipe Top Rail

D Lifetime L.E.D. Lights
- E** Spare Tire Mount

F (4) Tie Down Loops

G Treated Southern Pine Deck

H Professional & Durable Valspar Finish

I 3,500# Premium Axle with Quick Lubricating Hubs
- J** Steel Fenders

K Radial Tires on White Mod Wheels

L 4' Tall Rear Rampgate

M Coil Spring Assist on Rampgate

N Recessed Lighting & Protected Wiring

SU35 | Specifications



35SU			
Length	12' 14'	Axle	Premium 3,500# Axle w/ Quick Lubricating Hubs
Width	77"	Brakes	None
GVWR Rating	2,995#	Suspension	Multi-Leaf Spring
Empty Weight	1,080# (12') 1,170# (14')	Tires	ST205/75R-15 Load Range C
Payload	1,915# (12') 1,825# (14')	Wheels	15" x 5"; White Mod, 5 on 5 Bolt Pattern
Frame	3" x 2" x 3/16" Angle	Decking	2" Treated Pine
Cross Members	3" x 2" x 3/16" Angle	Lights	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance
Top Rail	2-3/8" OD Pipe Top Rail	Electric Plug	4-Way Flat w/ Loom
Uprights	2" x 2" Angle	Wiring	Protected Wiring Package
Coupler	2" A-Frame	Rampgate	4' Tall Rear Rampgate w/ Coil-Spring Assist
Jack	2,000# Top Wind, Set-Back Jack w/ Removable Sand Foot	Cargo Control	(4) Tie Down Loops Inside Bed
Fenders	9" x 32" Rolled Steel w/ Back		



4' tall spring-loaded rear ramp gate for easy loading.



Pipe top rail and channel tongue design for improved durability.



Set-back jack design to prevent tailgate damage on tow vehicle.



American-made Premium Axles with low-maintenance Quick Lubricating Hubs.



TU Series | Tandem-Axle Utility Trailers

The TU Series offers OrangeLine's widest range of hauling capacities, giving you more options to choose from. Each tandem-axle TU is designed for heavy-duty strength, with a pipe top rail to aid in cargo containment. For personal or commercial use, the TU excels at transporting compact tractors and other equipment around the farm, home or job site.

Premium features add convenience and versatility: Side pocket ramps allow for easy loading/unloading, and stow neatly out of the way when you don't need them. A set-back jack raises and stabilizes the trailer while protecting your tailgate. And long-lasting LED lights ensure safer operation for the long haul.



- TU60 | Tandem Axle, Pipe Top Utility Trailer
- TU70 | Tandem Axle, Pipe Top Utility Trailer
- TU10 | Pro Series Tandem Axle, Pipe Top Utility Trailer
- TU14 | Heavy-Duty Tandem Axle, Pipe Top Utility Trailer



Standard TU-Series Features

- A

Adjustable Coupler (Not on TU60 Model)
- B

Durable Pipe Top Rail
- C

Set-Back Jack Design
- D

Wrap Channel Tongue (Not on TU60 Model)
- E

Lifetime L.E.D. Lights
- F

Spare Tire Mount
- G

Professional and Durable Valspar Finish
- H

Treated Southern Pine Deck
- I

(6) Tie Down Pockets
- J

Premium Axle with Quick Lubricating Hubs
- K

Forward Self-Adjusting Electric Brakes
- L

Radial Tires on White Mod Wheels
- M

4' Slide-Out Ramp Package
- N

Recessed Lighting & Protected Wiring

TU Series | Specifications



	TU60	TU70
Length	16'	18' 20'
Width	77"	83"
GVWR Rating	6,000#	7,000#
Empty Weight	1,630#	2,060# (18') 2,140# (20')
Payload	4,370#	4,940# (18') 4,860# (20')
Frame	3" x 2" x 3/16" Angle	4" x 3" x 1/4" Angle
Cross Members	3" x 2" x 3/16" Angle	3" x 2" x 3/16" Angle
Top Rail	2-3/8" OD Pipe Top Rail	2-3/8" OD Pipe Top Rail
Uprights	2" x 2" Angle	3" x 2" x 3/16" Angle
Coupler	2" A-Frame	Adjustable, 2" Forged Coupler
Jack	2,000# Top Wind, Set-Back Jack w/ Removable Sand Foot	2,000# Top Wind, Set-Back Jack w/ Removable Sand Foot
Fenders	9" x 72" Rolled Steel w/ Back	9" x 72" Rolled Steel w/ Back
Axle	Premium 3,500# Axles w/ Quick Lubricating Hubs	Premium 3,500# Axles w/ Quick Lubricating Hubs
Brakes	Forward Self-Adjusting Electric Brakes on All Hubs	Forward Self-Adjusting Electric Brakes on All Hubs
Suspension	Multi-Leaf Spring w/ Equalizer	Multi-Leaf Spring w/ Equalizer
Tires	ST205/75R-15 Load Range C	ST205/75R-15 Load Range C
Wheels	15" x 5"; White Mod, 5 on 5 Bolt Pattern	15" x 5"; White Mod, 5 on 5 Bolt Pattern
Decking	2" Treated Pine	2" Treated Pine
Lights	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance
Electric Plug	7-Way RV Style	7-Way RV Style
Wiring	Protected Wiring Package	Protected Wiring Package
Ramps	4' Slide-In Ramps (Side Pockets)	4' Slide-In Ramps (Side Pockets)
Cargo Control	(6) Tie Down Pockets Along Sides	(6) Tie Down Pockets Along Sides

	TU10	TU14
Length	20'	20'
Width	83"	83"
GVWR Rating	9,990#	14,000#
Empty Weight	2,380#	3,040#
Payload	7,610#	10,960#
Frame	5" x 3" x 1/4" Angle	5" x 3" x 5/16" Angle
Cross Members	3" x 2" x 3/16" Angle	3" Channel
Top Rail	2-7/8" OD Pipe Top Rail	2-7/8" OD Pipe Top Rail
Uprights	3" x 2" x 3/16" Angle	3" x 2" x 3/16" Angle
Coupler	Adjustable, 2-5/16" Demco EZ Latch Coupler	Adjustable, 2-5/16" Demco EZ Latch Coupler
Jack	8,000# Top Wind, Set-Back Jack w/ Drop Leg	8,000# Top Wind, Set-Back Jack w/ Drop Leg
Fenders	9" x 72" Steel, Teardrop Style w/ Back	9" x 72" Double-Broke Diamond Plate Steel
Axles	Premium 5,200# Axles w/ Quick Lubricating Hubs	Premium 7,000# Axles w/ Quick Lubricating Hubs
Brakes	Forward Self-Adjusting Electric Brakes on All Hubs	Forward Self-Adjusting Electric Brakes on All Hubs
Suspension	Multi-Leaf Spring w/ Equalizer	Multi-Leaf Slipper Spring w/ Equalizer
Tires	ST225/75R-15 Load Range D	ST235/80R-15 Load Range E
Wheels	15" x 6"; White Mod, 6-Lug	16" x 6"; White Mod, 8-Lug
Decking	2" Treated Pine	2" Treated Pine
Lights	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance
Electric Plug	7-Way RV Style	7-Way RV Style
Wiring	Protected Wiring Package	Protected Wiring Package
Ramps	4' Slide-In Ramps (Side Pockets)	4' Slide-In Ramps (Side Pockets)
Cargo Control	(6) Tie Down Pockets Along Sides	(6) Tie Down Pockets Along Sides



Stowable slide-in ramp package allows great versatility when loading equipment.



Durable pipe top rail for added strength.



American-made Premium Axles with low-maintenance Quick Lubricating Hubs.



Forward Self-Adjusting Electric Brakes on all hubs for improved safety and stopping power.





TH Series | Tandem-Axle Tractor Haulers

Enjoy larger hauling capacities and exceptional versatility with the tandem-axle TH Series. Thanks to its open-sided design and low-profile angle iron frame, the TH provides easier access to the deck for rear or side loading. Nev-R-Adjust brakes on all hubs mean the TH models are legal for commercial use throughout the U.S., as well. For farming or construction applications, the TH hauls compact tractors and loaders with ease.

TH70 | Tandem Axle,
Pipe Top Utility Trailer

TH10 | Pro Series Tandem Axle,
Pipe Top Utility Trailer



Standard TH-Series Features

- A

Adjustable Forged Coupler
- B

Square Tubing Front Stop Rail
- C

Lifetime L.E.D. Lights
- D

Wrapped Channel Tongue
- E

Tie Down Pockets Along Sides
- F

Spare Tire Mount
- G

Professional & Durable Valspar Finish
- H

Treated Southern Pine Deck
- I

Premium Brake Axles with Quick Lubricating Hubs
- J

Radial Tires on White Mod Wheels
- K

Removable Double Broke Diamond Plate Steel Fenders
- L

Forward Self-Adjusting Electric Brakes
- M

4' Slide-Out Ramps
- N

Recessed Lighting & Protected Wiring

TH Series | Specifications



	TH70	TH10
Length	18' 20'	20'
Width	83"	83"
GVWR Rating	7,000#	9,990#
Empty Weight	1,910# (18') 2,060# (20')	2,280#
Payload	5,090# (18') 4,940# (20')	7,710#
Frame	5" x 3" x 5/16" Angle	6" x 3-1/2" x 5/16" Angle
Cross Members	3" x 2" x 3/16" Angle	3" x 2" x 3/16" Angle
Front Stop Rail	Square Tubing Front Stop Rail	Square Tubing Front Stop Rail
Coupler	Adjustable, 2" Forged Coupler	Adjustable, 2-5/16" Forged Coupler
Jack	2,000# Top Wind, Set-Back Jack w/ Removable Sand Foot	8,000# Top Wind, Set-Back Jack w/ Drop Leg
Fenders	Removable 9" x 72" Double-Broke Diamond Plate Steel	Removable 9" x 72" Double-Broke Diamond Plate Steel
Axles	Premium 3,500# Axles w/ Quick Lubricating Hubs	Premium 5,200# Axles w/ Quick Lubricating Hubs
Brakes	Forward Self-Adjusting Electric Brakes on All Hubs	Forward Self-Adjusting Electric Brakes on All Hubs
Suspension	Multi-Leaf Spring w/ Equalizer	Multi-Leaf Spring w/ Equalizer
Tires	ST205/75 R-15 Load Range C	ST225/75 R-15 Load Range D
Wheels	15" x 5"; White Mod, 5 on 5 Bolt Pattern	15" x 6"; White Mod, 6-Lug
Decking	2" Treated Pine	2" Treated Pine
Lights	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance
Electric Plug	7-Way RV Style	7-Way RV Style
Wiring	Sealed, Modular Wiring Harness	Sealed, Modular Wiring Harness
Ramps	4' Slide-In Ramps (Side Pockets)	4' Slide-In Ramps (Side Pockets)
Cargo Control	(8) Tie Down Pockets Along Sides	(8) Tie Down Pockets Along Sides



Low-profile angle iron frame for easy loading.



Stowable slide-in ramp package allows great versatility when loading equipment.



Adjustable coupler makes changing the coupler height for different tow vehicles quick and easy.



Heavy-duty diamond plate steel fenders are durable and strong.



EQ Series | Tandem-Axle Equipment Haulers

The super-duty EQ Series is ideal for hauling Kubota Commercial Equipment models. Every EQ trailer features a heavy-duty channel-iron frame with wrapped tongue to support larger weight capacities, and an open-side design that lends versatility for rear or side deck access. A cleated dovetail and rear stand-up ramps make for easier loading/unloading, while full-length rubrails with stake pockets and 6 D-rings aid in securing all types of cargo and equipment.

EQ14 | Heavy-Duty Tandem Axle Equipment Hauler

EQ16 | Super-Duty Tandem Axle Equipment Hauler



Standard EQ-Series Features

- A

Adjustable Demco EZ Latch Coupler
- B

12,000# Side Wind, Set-Back Jack w/ Drop Leg
- C

Zip Breakaway Cable
- D

Wrapped Channel Tongue with Storage Tray
- E

Square Tubing Front Stop Rail with Integrated Spare Tire Mount
- F

Lifetime L.E.D. Lights
- G

(6) D-Rings
- H

Rubrail & Tie Down Pockets Along Sides
- I

Professional & Durable Valspar Finish
- J

Treated Southern Pine Deck
- K

Premium Brake Axles
- L

Radial Tires on White Mod Wheels
- M

Removable Double Broke Diamond Plate Steel Fenders
- N

Forward Self-Adjusting Electric Brakes on All Hubs
- O

3' Cleated Dovetail & Stand-Up Equipment Ramps

EQ Series | Specifications




	EQ14	EQ16
Length	17' + 3"	17' + 3"
Width	83"	83"
GVWR Rating	14,000#	17,500#
Empty Weight	2,950#	3,710#
Payload	11,050#	13,790#
Frame	6" Channel	8" Channel
Cross Members	3" Channel	3" Channel
Front Stop Rail	Square Tubing Front Stop Rail	Square Tubing Front Stop Rail
Dovetail	3' Cleated Dovetail	3' Cleated Dovetail
Coupler	Adjustable, 2-5/16" Demco EZ Latch Coupler	Adjustable, 2-5/16" Demco EZ Latch Coupler
Jack	12,000# Side Wind, Set-Back Jack w/ Drop Leg	12,000# Side Wind, Set-Back Jack w/ Drop Leg
Fenders	Removable 9" x 72" Double-Broke Diamond Plate Steel	Removable 9" x 72" Double-Broke Diamond Plate Steel
Axles	Premium 7,000# Axles w/ Quick Lubricating Hubs	Premium 8,000# D80N Axles w/ Oil Bath Hubs
Brakes	Forward Self-Adjusting Electric Brakes on All Hubs	Forward Self-Adjusting Electric Brakes on All Hubs
Suspension	Multi-Leaf Slipper Spring w/ Equalizer	Multi-Leaf Slipper Spring w/ Equalizer
Tires	ST235/80 R-16 Load Range E	ST215/75 R-17.5 Load Range H
Wheels	16" x 6"; White Mod, 8-Lug	17.5" x 6.75"; White Mod, 8-Lug
Decking	2" Treated Pine	2" Treated Pine
Lights	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance	Recessed, L.E.D. D.O.T. Stop, Tail, Turn & Clearance
Electric Plug	7-Way RV Style	7-Way RV Style
Wiring	Sealed, Modular Wiring Harness	Sealed, Modular Wiring Harness
Ramps	4' Tall Knee Ramps	5' Tall Heavy-Duty Stand-Up Ramps
Cargo Control	Rubrail & Tie Down Pockets Along Sides + (6) D-Rings	Rubrail & Tie Down Pockets Along Sides + (6) D-Rings



High-tensile channel iron frame design provides long-lasting performance.



Integrated storage tray in tongue provides storage solutions.



Full-length rubrail & tie down pockets as well as (6) D-rings for optimal cargo control and tie-down options.



Cleated dovetail and stand-up equipment ramps allow for a low loading angle of equipment.



OrangeLine Trailers may be available through your local Kubota dealership.
Contact your nearest Kubota dealer or contact us at sales@orangelinetrailers.com for more information.

www.orangelinetrailers.com